

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

CQ6230D

Precision ground and hardened bedways



Specification	CQ6230D		CQ6230D (Variable-speed)	
	METRIC	INCH	METRIC	INCH
Swing over bed	300mm	12"	300mm	12"
Swing over cross slide	178mm	7"	178mm	7"
Swing in gap diameter	430mm	17"	430mm	17"
Length of workpiece	714/914mm	28"/36"	914mm	36"
Length of turning	560/760mm	22"/30"	760mm	30"
Spindle bore	38mm	1-1/2"	38mm	1-1/2"
Taper of spindle bore	MT NO. 5		MT NO. 5	
Range of spindle speed(9 steps)	60~1500r/min or 60~2000r/min		60~400r/min or 380~2200r/min	
Quill taper	MT NO. 3		MT NO. 3	
Range of metric threads to be cut(26 kinds)	0.4~7mm		0.4~7mm	
Range of inch threads to be cut(34 kinds)	4~56T.P.I		4~56T.P.I	
Pitches of three feed leadscrews	3mm	8T.P.I	3mm	8 T.P.I
Longitudinal feed per revolution of spindle(32 kinds)	0.052~1.392	0.002-0.0548"	0.052~1.392	0.002-0.0548"
Cross feed per revolution of spindle(32kinds)	0.014~0.38	0.0007~0.0187"	0.014~0.38	0.0007~0.0187"
Max. longitudinal travel of saddle	600/800mm	23-1/2"/31-1/2"	800mm	31-1/2"
Max. travel of cross slide	160mm	5-5/16"	160mm	5-5/16"
Max. travel of top slide	85mm	3-1/4"	85mm	3-1/4"
Quill travel	95mm	3-3/4"	95mm	3-3/4"
Main motor power	1.5HP(1.1kW)		1.5HP(1.1kW)	
Motor frequency	60Hz or 50Hz		60Hz or 50Hz	
Motor voltage	380/415V/115/230V or 110/200V		380/415V/115/230V or 110/200V	
Overall dimensions(L x W x H)	160 x 73 x 127cm		160 x 73 x 127cm	
Net weight	480kg		480kg	
Packing size(L x W x H)	148/168 x 75 x 142cm		168 x 75 x 142cm	