

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

C6266/CQ6280



Specification	Model	
	C6266	CQ6280
Swing over bed	660mm(26")	800mm(31-1/2")
Swing over cross slide	440mm(17-5/16")	800mm(31-1/2")
Swing in gap diameter	900mm(35-7/16")	1035mm(40-3/4")
Distance between centers	1500mm(60") 2000mm(80") 3000mm(120")	1500mm(60") 2000mm(80") 3000mm(120")
Valid length of gap	250mm(10")	
Width of bed	400mm(15-13/16")	
Spindle nose	D1-8	
Spindle bore	105mm(4-1/8")	
Taper of spindle bore	φ 113(1:20)	
Range of spindle speed	25 ~ 1600r/min	
Compound rest travel	230mm(9-1/8")	
Cross slide travel	368mm(14-1/2")	420mm(16-17/32")
Max. Section of tool	25x25mm(1"x1")	
Lead screw thread	12mm or 2T.P.I.	
Longitudinal feeds range	0.044 ~ 1.48mm/rev(0.00165" ~ 0.0550"/rev)	
Cross feeds range	0.022 ~ 0.74mm/rev(0.00083" ~ 0.02774"/rev)	
Threads metric pitches	54 kinds, 0.45 ~ 120mm	
Threads imperial pitches	54 kinds, 7/16 ~ 80T.P.I.	
Threads diametral pitches	42 kinds, 7/8 ~ 160DP	
Threads module pitches	46 kinds, 0.25 ~ 60MP	
Quill diameter	90mm(3-1/2")	
Quill travel	235mm(9-1/4")	
Quill taper	No.5 Morse	
Main motor power	7.5kW(10HP)3PH	
Coolant pump power	0.1kW(1/8HP)3PH	
Overall dimension(LxWxH)	321x123x160cm 371x123x160cm 471x123x160cm	321x123x167cm 371x123x167cm 471x123x167cm
packing size(LxWxH)	324x114x184cm 374x114x184cm 474x114x184cm	324x114x191cm 374x114x191cm 474x114x191cm
Net weight	3065kg 3345kg 3710kg	3175kg 3455kg 3820kg
Gross weight	3535kg 3835kg 4310kg	3695kg 4005kg 4495kg