

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

CQ6232G/36G

Variable speed model for optional



Model	CQ6232G	CQ6236G
Swing over bed	330mm(13")	360mm(14")
Swing over cross slide	198mm(7-25/32")	224mm(8-13/16")
Swing in gap diameter	476mm(18-3/4")	502mm(19-3/4")
Center height	166mm(6-1/2")	179mm(7")
Admits between	750mm(30") 1000mm(40")	750mm(30") 1000mm(40")
Bed width	187mm(7-3/8")	187mm(7-3/8")
Bed length	1405mm(55-5/16") 1655mm(65-1/8")	1405mm(55-5/16") 1655mm(65-1/8")
Bed height	290mm(11-13/32")	290mm(11-13/32")
Spindle bore	38mm(1-1/2") or 51mm	38mm(1-1/2") or 51mm
Spindle nose	D1-4"	D1-4"
Taper in nose	MT NO.5	MT NO.5
Speeds number	8	8
Range of spindle speed	70-2000r/min	70-2000r/min
Cross slide width	130mm(5-3/32")	130mm(5-3/32")
Cross slide travel	170mm(6-11/16")	170mm(6-11/16")
Compound rest width	80mm(3-1/8")	80mm(3-1/8")
Compound rest travel	95mm(3-9/16")	95mm(3-9/16")
Lead screw diameter	22mm(7/8")	22mm(7/8")
Lead screw thread	8T.P.I. or 3mm	8T.P.I. or 3mm
Feed rod diameter	19mm(3/4")	19mm(3/4")
Cutting tool max section	16mm x 16mm(5/8" x 5/8")	16mm x 16mm(5/8" x 5/8")
Threads imperial pitches	34 Nos.4-56 T.P.I	34 Nos.4-56 T.P.I
Threads metric pitches	26 Nos.0.4-7mm	26 Nos.0.4-7mm
Longitudinal feeds imperial	32Nos.0.002-0.548"/Rev	32Nos.0.002-0.548"/Rev
Longitudinal feeds metric	32Nos.0.052-0.392mm/Rev	32Nos.0.052-0.392mm/Rev
Cross feeds imperial	32Nos.0.007-0.0187"/Rev	32Nos.0.007-0.0187"/Rev
Cross feeds metric	32Nos.0.014-0.380mm/Rev	32Nos.0.014-0.380mm/Rev
Quill diameter	32mm(1-1/4")	32mm(1-1/4")
Quill travel	100mm(3-15/16")	100mm(3-15/16")
Quill taper	MT NO.3	MT NO.3
Main motor	1.5kW(2HP)	1.5kW(2HP)