

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

CQ6232D/36D

The thread category complete, not only cutting metric thread and imperial thread, but also cutting diametric thread and module thread ♦Three different length beds are available



Models	CQ6232D	CQ6236D
Swing over bed	330mm(13")	360mm(14")
Swing over cross slide	198mm(7-25/32")	224mm(8-13/16")
Swing in gap diameter	476mm(18-3/4")	502mm(19-3/4")
length in gap	210mm(8-1/4")	
Center height	166mm(6-1/2")	179mm(7")
Admits between	750mm(30") or 1000mm(40")	
Spindle bore	38mm(1-1/2") or 51mm	
Spindle nose	D1-4 or D1-5	
Taper in nose	No5 morse	
Speeds number	8	
Speeds range	70-2000r/min	
Cross slide travel	170mm(6-11/16")	
Compound rest travel	95mm(3-9/16")	
Lead screw thread	8T.P.I or 3mm pitch	
Feed rod diameter	19mm(3/4")	
Cutting tool max section	16mm x 16mm(5/8" x 5/8")	
Threads imperial pitches	42 Nos. 4-112T.P.I	
Threads metric pitches	44Nos. 0.1-7mm	
Threads diametral pitches	25Nos. 16-112DP	
Threads module pitches	34Nos. 0.1-1.75MP	
Longitudinal feeds imperial	24Nos. 0.00168-0.1175"/rev	
Longitudinal feeds metric	24Nos. 0.046-3.249mm/rev	
Cross feeds imperial	32Nos. 0.00046-0.03231"/rev	
Cross feeds metric	24Nos. 0.01-0.703mm/rev	
Quill diameter	32mm(1-1/4") or 42mm(1-21/32")	
Quill travel	100mm(3-15/16")	
Quill taper	No3 morse	
Main motor power	1.5kW(2HP)	
Coolant pump power	40W(1/16HP)	
Packing size(cm)	168 x 76 x 158(750mm) or 193 x 76 x 153(1000mm)	
NG/GW(kg)	510/630(750mm) or 540/645(1000mm)	