

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

CM6241/41V

Precision ground and hardened bedways



ITEMS	Model	
	CM6241X1000/1500	CM6241VX1000/1500
Swing over bed	410mm (16")	
Swing over cross slide	255mm (10")	
Swing in gap diameter	580(22")	
Height of center	205mm (8")	
Admits between	1000mm (40")/1500mm	
Width of bed	250mm (10")	
Cutting tool max section	20 × 20mm ($\frac{3}{4}$ " × $\frac{3}{4}$ ")	
Total travel of cross slide	210mm (8 $\frac{1}{2}$ ")	
Compound rest travel	140mm (5 $\frac{1}{2}$ ")	
Spindle bore	52mm (2")	
Spindle morse taper in bore	D1-6	
Lead screw thread	4 T.P.I	
Spindle speeds range	16 steps 45–1800R.P.M 30–550r/min or 550–3000r/min	
Threads imperial pitches	2–72T.P.I(45Nos)	
Threads metric pitches	0.2–14mm(39Nos)	
Longitudinal feeds	0.05–1.7mm/Rev(0.002"–0.067"/rev)	
Cross feeds	0.025–0.85mm(0.001"–0.0335"/rev)	
Range of module pitches	0.3–3.5MP(18Nos)	
Range of diametral pitches	8–44DP(21Nos)	
Tailstock quill diameter	50mm(2")	
Total travel of tailstock quill	120mm(4 $\frac{3}{4}$ ")	
Taper in tailstock quill	M.T.No.4	
Spindle drive motor	4P/8P,3PH 3.3/2.2kw	
Coolant pump motor	4P,3PH 90W	
Packing size (L × W × H)	206(81") (256) × 90(35 $\frac{7}{16}$ ") × 164cm(64 $\frac{9}{16}$ ")	
Net weight	1300kg or 1350kg/1550kg or 1600kg	
Gross weight	1500kg or 1555kg/1750kg or 1755kg	