

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

Z5040/Z5040E



Model UnitZ5040 MachinerypowerfeedZ5040E Electronicpower feed Max.drillingcapacitymm40
Max.tapping capacity (steel/castiron)mm22/24 Spindletaper—MT4 Spindlestroke mm180 Distance from spindle center to column surface mm350 Distance from spindle nose to worktable mm770
Distance from spindle nose to base mm1215 Spindle power feed range mm/rev 2steps/0.1,0.2
Spindle speeds range rpm50-1450 Number of speeds—18 Diameter of column mm150 Worktable size mm560×560
Dimensions of base mm735×510 T Width of T-slot mm18 T Distance of T-slot base mm200 Cooling pump W75
Main motor (2 speed motor) kW0.85/1.5 Packing size (L×W×H) mm2270×580×1100 / N.W/G.W Kg540/600
20' container Q'ty: sets 20

Features

- 2 speed strong power motor
- Automatic tools ejectors
- 2 steps power feed 0.1-0.2mm/rev
- Drilling tapping

Main Specifications

Model	Unit	Z5040 Machinery power feed	Z5040E Electronic power feed
Max.drilling capacity	mm	40	
Max.tapping capacity (steel/cast iron)	mm	22/24	
Spindle taper	—	MT4	
Spindle stroke	mm	180	
Distance from spindle center to column surface	mm	350	
Distance from spindle nose to worktable	mm	770	
Distance from spindle nose to base	mm	1215	
Spindle power feed range	mm/rev	2steps/0.1,0.2	
Spindle speeds range	rpm	50-1450	
Number of speeds	—	18	
Diameter of column	mm	150	
Worktable size	mm	560×560	
Dimensions of base	mm	735×510	
Width of T-slot	mm	18	
Distance of T-slot base	mm	200	
Cooling pump	W	75	
Main motor (2 speed motor)	kW	0.85/1.5	
Packing size (L×W×H)	mm	2270×580×1100	
N.W/G.W	Kg	540/600	
20' container Q'ty:	sets	20	