

Архангельск (8182)63-90-72

Астана (7172)727-132

Астрахань (8512)99-46-04

Барнаул (3852)73-04-60

Белгород (4722)40-23-64

Брянск (4832)59-03-52

Владивосток (423)249-28-31

Волгоград (844)278-03-48

Вологда (8172)26-41-59

Воронеж (473)204-51-73

Екатеринбург (343)384-55-89

Иваново (4932)77-34-06

Ижевск (3412)26-03-58

Иркутск (395)279-98-46

Казань (843)206-01-48

Калининград (4012)72-03-81

Калуга (4842)92-23-67

Кемерово (3842)65-04-62

Киров (8332)68-02-04

Краснодар (861)203-40-90

Красноярск (391)204-63-61

Курск (4712)77-13-04

Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13

Москва (495)268-04-70

Мурманск (8152)59-64-93

Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12

Новокузнецк (3843)20-46-81

Новосибирск (383)227-86-73

Омск (3812)21-46-40

Орел (4862)44-53-42

Оренбург (3532)37-68-04

Пенза (8412)22-31-16

Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15

Рязань (4912)46-61-64

Самара (846)206-03-16

Санкт-Петербург (812)309-46-40

Саратов (845)249-38-78

Севастополь (8692)22-31-93

Симферополь (3652)67-13-56

Смоленск (4812)29-41-54

Сочи (862)225-72-31

Ставрополь (8652)20-65-13

Сургут (3462)77-98-35

Тверь (4822)63-31-35

Томск (3822)98-41-53

Тула (4872)74-02-29

Тюмень (3452)66-21-18

Ульяновск (8422)24-23-59

Уфа (347)229-48-12

Хабаровск (4212)92-98-04

Челябинск (351)202-03-61

Череповец (8202)49-02-64

Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

Z5032



Main Specifications: Max.drilling capacitymmcasting32steel25Max.tapping capacitymmcasting22steel16Spindle taper—

MT4Spindle stroke mm160Distance from spindle center to column surface mm300Distance from spindle nose to worktable mmMax:720Distance from spindle nose to base mm1200Vertical travel of worktable mm700Spindle speeds range rpm75-3200Number of speeds—

12Speed power feed range mm/r0.06/0.12/0.18Diameter of column mm125Worktable size mm460×460Base size mm620×450Width of T-slot mm14Distance of T-slot base mm160Main motor (2 speed motor) KW1.5/1.1kW Packing size (L×W×H) mm2100×400×640Net weight KG350

Main Specifications :

Max.drilling capacity	mm	casting	32
		steel	25
Max.tapping capacity	mm	casting	22
		steel	16
Spindle taper	—	MT4	
Spindle stroke	mm	160	
Distance from spindle center to column surface	mm	300	
Distance from spindle nose to worktable	mm	Max:720	
Distance from spindle nose to base	mm	1200	
Vertical travel of worktable	mm	700	
Spindle speeds range	rpm	75-3200	
Number of speeds	—	12	
Speed power feed range	mm/r	0.06/0.12/0.18	
Diameter of column	mm	125	
Worktable size	mm	460×460	
Base size	mm	620×450	
Width of T-slot	mm	14	
Distance of T-slot base	mm	160	
Main motor (2 speed motor)	KW	1.5/1.1kW	
Packing size (L×W×H)	mm	2100×400×640	
Net weight	KG	350	