

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

X6330

Z axis: box way Y axis: box way



Z axis: box way Y axis: box way

Unit:mm

Item / Model		X6330	X6330A
Table size		305 × 1370(12" × 54")	305 × 1500(12" × 58")
Long travel		870	1000
Cross travel		380	
Vertical travel		430	
T-slot No.and size		3 × 16	
Ram travel		500	
Distance from spindle nose to table surface		0~435	
Spindle hole taper		(standard):ISO40	
Spindle travel		127	
Spindle speed		(standard):	(shiftgrade) 50HZ:65~4500 60HZ:80~5440
		(optional):	(variable)65~3750
Auto.quill feed		(threesteps):0.04(0.0015")/0.08(0.003")/0.15(0.006")mm/revolution	
Spindle motor		3.75kW/5HP	
Head swivel		90°	
Head tilting		45°	FIX
Dimension of package	One miller per case	1566 × 1650 × 2080	
	Two miller per case	1720 × 1800 × 2175	
	Three miller per case		
G.W/set		1700	1750