

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

Metalworking Machine S



Item / Model		S-13548	S-1654	S-2063	S-2063A	S-2473
Table	Table size (L x W/mm)	1370 x 330	1370 x 406	1600 x 510	1600 x 510	1854 x 610
	Table loading capability (kg)	400	800	1200	1200	1500
	T-slots (W/mm x No)	16 x 3	16 x 5	18 x 5	18 x 5	18 x 5
Travel	X-axis (mm)	800	1000	1200	1200	1500
	Y-axis (mm)	450	480	700	740	740
	Z-axis (mm)	480	600	600	740	700
	(X,Y,Z) Max. move speed (mm/min)	8000	8000	10000	10000	10000
	(X,Y,Z) Max. feed speed (mm/min)	3000	3000	4000	4000	4000
Spindle	Spindle speed (rpm/min)	RANGE 40-6000	RANGE 40-6000	RANGE 40-6000	RANGE 40-6000	RANGE 40-6000
	Spindle nose	BT40	BT40	BT40/BT50	BT40/BT50	BT40/BT50
	Spindle motor (kW)	5.5	7.5	7.5	7.5	7.5
	Servo motor (kW)	1.5	1.5	2.8	2.8	2.8
	Spindle quill diameter (mm)	φ 120	φ 150	φ 150/ φ 155	φ 150/ φ 155	φ 150/ φ 155
	Distance from spindle to column surface (mm)	160-640	80-680	60-660	60-800	80-780
Ball screws	X-axis (mm)	φ 32 x 5 P4 Double nuts	φ 32 x 5 P4 Double nuts	φ 40 x 10 P4 Double nuts	φ 40 x 10 P4 Double nuts	φ 40 x 10 P4 Double nuts
	Y-axis (mm)	φ 32 x 5 P4 Double nuts	φ 40 x 5 P4 Double nuts	φ 40 x 10 P4 Double nuts	φ 40 x 10 P4 Double nuts	φ 40 x 10 P4 Double nuts
	Z-axis (mm)	φ 32 x 5 P4 Double nuts	φ 40 x 5 P4 Double nuts	φ 40 x 10 P4 Double nuts	φ 40 x 10 P4 Double nuts	φ 40 x 10 P4 Double nuts
Three axis accuracy	Positioning accuracy	0.025mm	0.03mm	0.03mm	0.03mm	0.04mm
	Repeatability	0.012mm	0.016mm	0.016mm	0.016mm	0.02mm
(mm)	Semi-closure guard	2280 x 2250 x 2470	2500 x 2280 x 2650	2280 x 2900 x 2850	2280 x 2900 x 2950	2280 x 2900 x 2950
	Full-closure guard	3000 x 2280 x 2470	3300 x 2280 x 2650	3700 x 2800 x 2870	3700 x 2890 x 2970	4700 x 2800 x 2970
(kg)	Semi-closure guard	2600	3800	5000	5400	5200
	Full-closure guard	3400	4720	6400	6900	7500

※ The control system could be equipped by customer' order.