

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

Z5030

Headstock can rotated 360° and can tilted +-45°



Specifications

Max .Drilling capacity
Max. tapping diameter
Working table size
Dimension of base
Diameter of column
Spindle stroke
Max distance spindle face to table
Max distance spindle face to base
Distance between spindle and column
Head tilt left and right
Spindle taper

Spindle speed range
1 Speed motor 1.1KW (standard):
2 Speed motor
0.85KW/1.1KW (optional):

Number of speeds
Auto spindle feeds (optional)
Cooling motor (optional)
N.W/G.W
Packing dimension
20'container Q'ty:

The design, descriptions and specifications are subject to change without notice.

Features :

Drilling, tapping, boring, reaming
Gear driving and strong cutting power
Headstock can rotated 360° and can tilted +-45°
Heavy-duty tapered roller bearing spindle
Positive spindle lock
Micro feed precision

Options:

“C”-Cooling system; “L” - Halogen light; “B”- CE electrical control box(tapping);
“F”-Auto spindle feeder; “D”-2-step motor;
P1:Z5030
P2:Z5030(CF)

Units	Z5030
mm	32
	M20
mm	540×470
mm	650×450
mm	115
mm	120
mm	610
mm	1180
mm	260
	90°
	MT3 or MT4 or R8
rpm	75-1600
rpm	75-3200
(steps)	6 or 12 (optional)
mm/r	0.1/0.18/0.26
W	40
kg	340/390
mm	740×720×1830
sets	24