

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

Z5035

Auto spindle feeder, cooling system and halogen light are supply as standard



Specifications

Max. drilling diameter
Max. tapping diameter
Spindle taper
Spindle stroke
Distance from spindle center to column
Distance from spindle face to table
Distance from spindle face to base
Spindle speed (2 speed motor)
Number of speeds
Auto spindle feeds
Diameter of column
Table size
(Num of T-slot and width)
(Width of jaw, Max. Opening Capacity)
Base size
Machine motor
Packing dimension
N.W/G.W
20'container Q'ty:

Features

Drilling, tapping, boring, reaming
Gear driving and strong cutting power
2-step motor for wide spindle speed range
CE electrical control box(tapping)supply as standard
Auto spindle feeder, cooling system and halogen light are supply as standard
New-designed, worktable can be rotated 360 which is reliable and easy for use
Worktable including vice worktable and flat worktable on two sides
Gear head is fix type and can not be lifting and tilting.

Units	Z5035
mm	35
	M24
	MT3 orMT4
mm	130
mm	310
mm	85-685
mm	1140
rpm	75-3200
(steps)	12
mm/r	0.1/0.18/0.26
mm	125
mm	500×380
mm	2-14
mm	145, 130
mm	670×470
Kw	1.1/1.5
mm	810×570×2100
kg	450/490
sets	28