

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://qianzhu.nt-rt.ru/> || quz@nt-rt.ru

ZX40H

The design, descriptions and specifications are subject to change without notice.



Specifications

Max .Drilling capacity

Face mill capacity

End mill capacity

Working table size (standard):

Working table travel (standard):

Working table size(optional):

Working table travel(optional):

Dimension of base

Diameter of column

T-Slot size

Spindle stroke

Max distance from spindle face to table

Max distance from spindle face to base

Distance between spindle and column

Head tilt left and right

Spindle taper

Spindle speed 1 Speed motor 1.1KW (standard):

range 2 Speed motor 0.85KW/1.1KW (optional):

Number of speeds

Auto spindle feeds(optional):

Cooling motor(optional):

N.W/G.W

Packing dimension

20'container Q'ty:

The design, descriptions and specifications are subject to change without notice.

Features :

Milling drilling, tapping, boring, reaming

Gear driving and strong cutting power

Headstock can rotated 360°and can tilted +-45°

Heavy-duty tapered roller bearing spindle

Positive spindle lock

Adjustable gibs on table

Micro feed precision

Options:

“C”-Cooling system; “L”- Halogen light; “B”- CE electrical control box(tapping);

“F”-Auto spindle feeder;“P”-Work table power feeder; “D”-2-step motor;

“R”-Digital read out (DRO);

P1:ZX40H

P2:ZX40H(BCDFLP)

Units

mm

mm

mm

mm

mm

mm

mm

mm

mm

mm

mm

mm

mm

mm

rpm

rpm

(steps)

mm/r

W

kg

mm

sets

ZX40H

(Iron)40/(Steel)32

80

32

600×190

370×190

730×210

500×190

650×450

115

12

120

610

1180

260mm

90°

MT3 or MT4 or R8

75-1600

75-3200

6 or 12 (optional)

0.1/0.18/0.26

40

340/390

830×760×1850

21